

Product datasheet

Specifications



Schneider Electric EASY UPS BVS 1000VA, Schuko outlet

BVS1000I-GR

Main

Product or component type	Uninterruptible power supply (UPS)
Battery type	Lead-acid battery
Topology	Line interactive
Quantity per set	Set of 1
Reset	Automatic reset
Range of product	Easy UPS 1Ph BVS Series

Complementary

Type of installation	Indoor
Surge Energy	156 J
Type of signal	Stepped approximation to a sinewave
Protection device type	Surge protection device (SPD) Miniature circuit breaker (MCB) Fuse
Input voltage	230 V AC
Output voltage	230 V
IP degree of protection	IP20
Transfer time	6 ms typical : 10 ms maximum
Network frequency	45...65 Hz
Power range	1000 VA 600 W
Electrical connection	Input: 1 inlet Schuko CEE 7/P Output: 4 outlet Schuko CEE 7
Local signalling	Alarm, distinctive for low battery Alarm, continuous or intermittent tone for overload LED for battery status
Number of batteries	1
Charging time	8 h
Battery voltage	12 V
Battery capacity	9.0 Ah
Battery life	5 year(s)
Net weight	5.7 kg

Height	92.5 mm
Width	160.5 mm
Depth	305 mm

Environment

Relative humidity	0...90 %, non-condensing
Operating altitude	0...6561 ft
Ambient air temperature for operation	0...40 °C
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Product certifications	CE

Physical

Mounting support	Wall Floor
-------------------------	---------------

Packing Units

Unit Type of Package 1	PCE
Package 1 Length	9.246 cm
Number of Units in Package 1	1
Package 1 Width	16.51 cm
Package 1 Height	30.505 cm
Package 1 Weight	5.702 kg
SCC14	10731304338403

Offer Sustainability

EU RoHS Directive	Under investigation
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	2 years
-----------------	---------