



Schneider Electric EASY UPS BVS 650VA, Schuko outlet

BVS650I-GR

M	a	ın

Product or component type	Uninterruptible power supply (UPS)	
Battery type	Lead-acid battery	
Topology	Line interactive	
Quantity per set	Set of 1	
Reset	Automatic reset	
Range of product	Easy UPS 1Ph BVS Series	

Complementary	
Type of installation	Indoor
Surge Energy	156 J
Type of signal	Stepped approximation to a sinewave
Protection device type	Surge protection device (SPD) Miniature circuit breaker (MCB) Fuse
Input voltage	230 V AC
Output voltage	230 V
IP degree of protection	IP20
Transfer time	6 ms typical : 10 ms maximum
Network frequency	4565 Hz
Power range	650 VA 375 W
Electrical connection	Input: 1 inlet Schuko CEE 7/P Output: 4 outlet Schuko CEE 7
Local signalling	Alarm, distinctive for low battery Alarm, continuous or intermittent tone for overload LED for battery status
Number of batteries	1
Charging time	8 h
Battery voltage	12 V
Battery capacity	7.0 Ah
Battery life	5 year(s)
Net weight	4.5 kg

Height	92.5 mm
Width	160.5 mm
Depth	305 mm
Environment	
Relative humidity	090 %, non-condensing
Operating altitude	06561 ft
Ambient air temperature for operation	040 °C
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Product certifications	CE
Physical	
Mounting support	Wall Floor
Packing Units	
Unit Type of Package 1	PCE
Package 1 Length	9.246 cm
Number of Units in Package 1	1
Package 3 Width	80 cm
Package 3 Weight	244.22 kg
Package 2 Width	39 cm
Package 2 Height	25 cm
Package 2 Weight	20.35 kg
Number of Units in Package 3	48
Unit Type of Package 3	P12
Package 3 Height	91 cm
Package 3 Length	120 cm

Package 1 Weight	4.5 kg
Number of Units in Package 2	4
Unit Type of Package 2	CAR

16.51 cm

30.505 cm

Package 2 Length 58 cm

SCC14 10731304338489

Offer Sustainability

Package 1 Width

Package 1 Height

REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration

Product out of China RoHS scope. Substance declaration for your information

WEEE

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty

2 years