

# Product datasheet

Specifications

**APC**



## APC Easy UPS BVX 700VA, 230V, AVR, Schuko Sockets

BVX700LI-GR

### Overview

Lead time Usually in Stock

### Main

Input voltage 230 V AC 1 phase

Output voltage 230 V AC 1 phase

Rated power in W 360 W

Rated power in VA 700 VA

Plug standard Schuko

Nb of power socket outlets 2 Schuko

Cable length 1.22 m

Number of cables 1

Battery type Lead-acid battery

Provided equipment User manual

### General

Max runtime 120 min

Number of power module free slots 0

Number of power module filled slots 0

Redundant No

UPS size WS

### Physical

Colour Black

Height 13.8 cm

Width 9.8 cm

Depth 31 cm

Net weight 4.2 kg

Mounting support Floor

Mounting preference No preference

|                    |                    |
|--------------------|--------------------|
| Mounting mode      | Not rack-mountable |
| Two post mountable | 0                  |
| USB compatible     | No                 |

## Input

|                      |                                |
|----------------------|--------------------------------|
| Network frequency    | 50/60 Hz +/- 5 Hz auto sensing |
| Input voltage limits | 140...300 V 230 V AC           |
| Cos phi              | 0.51                           |

## Output

|                                  |                                     |
|----------------------------------|-------------------------------------|
| Maximum configurable power in W  | 360 W                               |
| Output frequency                 | 50/60 Hz +/- 1 Hz sync to mains     |
| UPS type                         | Line interactive                    |
| Wave type                        | Stepped approximation to a sinewave |
| Full load runtime                | 00:00:01 360 W                      |
| Graph display                    | 1                                   |
| Half load runtime                | 00:06:00 180 W                      |
| Maximum configurable power in VA | 700 VA                              |
| Transfer time                    | 6 ms typical : 10 ms maximum        |

## Conformance

|                             |                        |
|-----------------------------|------------------------|
| Product certifications      | CE<br>CB               |
| Equipment protection policy | Lifetime : 50000 euros |

## Environmental

|                                       |                         |
|---------------------------------------|-------------------------|
| Ambient air temperature for operation | 0...40 °C               |
| Relative humidity                     | 0...95 % non-condensing |
| Operating altitude                    | 0...3000 m              |
| Ambient air temperature for storage   | -15...40 °C             |
| Storage Relative Humidity             | 0...95 % Non-condensing |
| Storage altitude                      | 0...3000 m              |
| Acoustic level                        | 40 dBA                  |
| IP degree of protection               | IP20                    |

## Batteries & Runtime

|                                |   |
|--------------------------------|---|
| Number of battery filled slots | 0   |
| Number of battery free slots   | 0   |
| Battery recharge time          | 8 h   |
| Battery voltage                | 12 V  |
| Battery capacity               | 7.0 Ah  |
| Battery life                   | 2...3 year(s)   |
| Replacement battery            | <a href="#">APCRBC110</a>  |

---

|                  |   |
|------------------|---|
| Extended runtime | 0 |
|------------------|---|

---

## Communications & Management

---

|               |   |
|---------------|---|
| Control panel | LED Status display with on line : on battery          |
| Alarm         | Alarm when on battery : distinctive low battery alarm |

---

---

## Surge Protection and Filtering

---

|                   |       |
|-------------------|-------|
| Surge energy rate | 273 J |
|-------------------|-------|

---

---

## Packing Units

---

|                  |                |
|------------------|----------------|
| Package 1 Weight | 4.5 kg         |
| Package 1 Height | 22.2 cm        |
| Package 1 Width  | 14.2 cm        |
| Package 1 Length | 34.6 cm        |
| SCC14            | 10731304404580 |

---

---

## Offer Sustainability

---

|                   |  |
|-------------------|--|
| EU RoHS Directive | Compliant<br><a href="#">EU RoHS Declaration</a> |
|-------------------|--|

---

---

## Contractual warranty

---

|          |                           |
|----------|---------------------------|
| Warranty | 2 years repair or replace |
|----------|---------------------------|

---