

# Product data sheet

Specifications



## APC Smart-UPS On-Line, 5kVA, Tower, 230V, 6x C13+4x C19 IEC outlets, Network Card+SmartSlot, Extended runtime, W/O rail kit

SRT5KXLI

### Overview

Presentation	High density, double-conversion on-line power protection with scalable runtime.
Lead time	Usually in Stock

### Main

Main Input Voltage	230 V
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	4500 W
Rated power in VA	5000 VA
Output connection type	6 IEC 60320 C13 2 IEC Jumpers 4 IEC 60320 C19
Battery type	Lead-acid battery
Provided equipment	CD with software Communication cable Documentation CD Installation guide Removable support feet Temperature probe USB cable Warranty card Web/SNMP management card

### General

Product web sub-family	High density
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

### Physical

Colour	Black
Height	43.2 cm

Width	13 cm
Depth	71.94 cm
Net weight	54.43 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Rack-mounted with kit
Two post mountable	0
USB compatible	Yes

## Input

Network frequency	40...70 Hz auto-sensing
Number of input connectors	1 hard wire 3-wire (1P + N + E)
Input voltage limits	100...275 V adjustable (half load)

## Output

Maximum configurable power in W	4500 W
Harmonic distortion	Less than 2 %
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Crest factor	3 : 1
UPS type	Double conversion online
Wave type	Sine wave
Bypass type	Internal bypass (automatic and manual)
Maximum configurable power in VA	5000 VA

## Conformance

Product certifications	CE EAC IRAM RCM VDE
Marking	CE Mark
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	Non-condensing 0...95 %
Storage altitude	0.00...15240.00 m
Acoustic level	55 dBA
Heat dissipation	931 Btu/h
IP degree of protection	IP20

## Batteries & Runtime

Number of battery filled slots	2
Number of battery free slots	0
Battery recharge time	1.5 h
Number of battery replacement quantity	1
Battery voltage	192 V
Battery charger power	560 W rated
Battery power in VAH	845 VAh runtime
Battery life	3...5 year(s)
Battery option	SRT192BP 1 2535 VAh SRT192BP 2 4225 VAh SRT192BP 3 5915 VAh SRT192BP 4 7605 VAh SRT192BP 5 9295 VAh SRT192BP 6 10985 VAh SRT192BP 8 14365 VAh SRT192BP 10 17745 VAh
Extended runtime	1

## Communications & Management

Free slots	1
Preinstalled device	Network management card 3 with environmental monitoring
Control panel	Multifunction LCD status and control console
Alarm	Audible and visible alarms prioritized by severity
Emergency power off	Yes

## Surge Protection and Filtering

Surge energy rate	480 J
-------------------	-------

## Packing Units

Package 1 Height	33 cm
Package 1 Width	61 cm
Package 1 Length	96 cm
Package 1 Weight	63.6 kg
Unit Type of Package 2	P12
Number of Units in Package 2	1
Package 2 Height	80 cm
Package 2 Width	80 cm
Package 2 Length	120 cm
Package 2 Weight	75 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes

<b>RoHS exemption information</b>	<a href="#">Yes</a>
<b>Environmental Disclosure</b>	<a href="#">Product Environmental Profile</a>
<b>Circularity Profile</b>	<a href="#">End of Life Information</a>
<b>WEEE</b>	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
<b>California proposition 65</b>	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
<b>Optimized Energy Efficiency</b>	Energy efficient product
<b>Take-back</b>	Take-back program available

## Contractual warranty

<b>Warranty</b>	3 years repair or replace (excluding battery) and 2 years for battery
-----------------	---