Product datasheet

Specifications

Easy UPS On-Line SRVS Tower Battery Pack for 2/3kVA Extended Runtime Model, 72V

SRVS72BP-9A

Overview

Lead time	Usually in Stock

Main

Battery type	Lead-acid battery
Provided equipment	User manual Battery cable

Batteries & Runtime

Number of battery blocks per string	6
Device mounting	Floor mounted
Number of battery filled slots	0
Number of battery free slots	0
Battery voltage	72 V

Physical

Colour	Black
Height	33.6 cm
Width	19 cm
Depth	42.5 cm
Net weight	38 kg
Mounting mode	Not rack-mountable
USB compatible	No

Conformance

Product certifications	CE UKCA EAC EN/IEC 62040-1

Environmental

Ambient air temperature for operation	0…40 °C
Relative humidity	0…95 % non-condensing

Operating altitude	0...3000 m
Ambient air temperature for storage	-15…40 °C
Storage Relative Humidity	0…95 % non-condensing
Storage altitude	0…15000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	32.5 cm
Package 1 Width	23.5 cm
Package 1 Length	56.5 cm
Package 1 Weight	40.2 kg

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	2 years repair or replace

Recommended replacement(s)

Life Is On | Schneider Electric