

Product data sheet

Specifications



APC Smart-UPS X, Line Interactive, 2200VA, Rack/tower convertible 2U, 200V-240V, 8x C13+1x C19 IEC, SmartSlot, Extended runtime

SMX2200RMHV2U

Overview

Presentation Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.

Lead time Usually in Stock

Main

Main Input Voltage 208 V
230 V

Other Input Voltage 220 V
240 V

Main Output Voltage 208 V
230 V

Other Output Voltage 220 V
240 V

Rated power in W 1980 W

Rated power in VA 2200 VA

Input Connection Type IEC 320 C20
Schuko CEE 7 / EU1-16P
BS1363A British

Output connection type 8 IEC 320 C13
2 IEC Jumpers
1 IEC 320 C19

Number of rack unit 2U

Cable length 1.83 m

Number of cables 1

Battery type Lead-acid battery

Provided equipment CD with software
Documentation CD
Smart UPS signalling RS-232 cable
User manual
USB cable
Rack mounting brackets

General

Number of power module 1750

Number of power module filled slots 0

Number of power module free slots 0

Product web sub-family	Extended run
Redundant	No

Physical

Colour	Black
Height	8.5 cm
Width	43.2 cm
Depth	66.7 cm
Net weight	37.32 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted
Two post mountable	0
USB compatible	Yes

Input

Input voltage limits	140...280 V
Network frequency	50/60 Hz +/- 3 Hz auto-sensing

Output

Harmonic distortion	Less than 5 %
Maximum configurable power in VA	2200 VA
Maximum configurable power in W	1980 W
Transfer time	2-4 ms 6 ms typical : 10 ms maximum
UPS type	Line interactive
Wave type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains

Conformance


Product certifications	CE CSA EAC IRAM RCM VDE
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Acoustic level	55 dBA
Heat dissipation	150 Btu/h
Operating altitude	0...10000 ft
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.00...15240.00 m

Relative humidity	0...95 %
Storage Relative Humidity	0...95 %

Batteries & Runtime

Extended runtime	1
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Battery life	3...5 year(s)
Replacement battery	APCRBC117 
Battery power in VAH	702 VAh runtime
Battery charger power	233 W rated
Battery option	SMX120RMBP2U 1 2106 VAh SMX120RMBP2U 2 3510 VAh SMX120RMBP2U 3 4914 VAh SMX120RMBP2U 4 6318 VAh SMX120RMBP2U 6 9126 VAh SMX120RMBP2U 8 11934 VAh SMX120RMBP2U 10 14742 VAh

Communications & Management

Control panel	LED status display with load and battery bar-graphs and on line : on battery : replace battery : and overload indicators Multifunction LCD status and control console
Emergency power off	Yes
Free slots	1
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

Surge Protection and Filtering

Surge energy rate	645 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.3 cm
Package 1 Width	59.6 cm
Package 1 Length	86.9 cm
Package 1 Weight	45.36 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	8
Package 2 Height	111 cm
Package 2 Width	100 cm
Package 2 Length	120 cm
Package 2 Weight	384 kg
Pallet unit layers	2

Pallet layers	4
---------------	---

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery, optional on-site warranties available, optional extended warranties available
----------	--

Recommended replacement(s)